



Pattern: **Castillo** Grade 2

Fabric Specifications	
Content	100% polyurethane
Weight (oz/lin yd)	22.9
Width (inches)	54
Ends (per inch)	
Picks (per inch)	
Horizontal Repeat (inches)	
Vertical Repeat (inches)	
Directional (yes or no)	
Railroaded (yes or no)	
Cleaning Code	W
Finish	Antimicrobial — Silver Based Ion Technology
Backing	87% polyester, 13% cotton
Certifications	
SCS Certified Indoor Advantage Gold	
Performance Characteristics	
Abrasion Resistance	ASTM D 4157
Abrasion Resistance (Double Rubs)	200,000
Tensile Strength	
Tensile Strength Warp (lbs)	
Tensile Strength Fill (lbs)	
Tear Strength	ASTM D 5034-95
Tear Strength Warp (lbs)	141
Tear Strength Fill (lbs)	78
Seam Slippage	ASTM D 4034
Seam Slippage Warp (lbs)	50
Seam Slippage Fill (lbs)	69
Brush Pill	ASTM D 3511
Brush Pill (Class)	5
Colorfastness to Crocking	AATCC 8
Colorfastness to Crocking Dry	Class 5
Colorfastness to Crocking Wet	Class 5
Colorfastness to Light	AATCC 16 option 1
Colorfastness (Hours)	40
Colorfastness (Class)	4
Flammability	
California Technical Bulletin 117 Section E (CS-191-53)	Passes
NFPA 260	Class 1
UFAC	Class 1

For samples call:
800-841-8111